

# SureShot™

## PRODUCT SPECIFICATIONS WIRELESS REMOTE CONTROLLER

### MECHANICAL

Control unit                    19" W x 1.75" H x 5" D, standard rack mount  
  Antenna extends 2" deeper if rear mounted rather than mounted outside  
Handheld Transmitter    1.625" W x .275" H x 1" D, plus 1.5" antenna

### ELECTRICAL/ELECTRONIC

Power: Control Unit: 12V DC @ 56 mA quiescent  
  Transmitter: CR2032 lithium battery  
All solid state components

### ENVIRONMENTAL

Control Unit    0 – +50°C

### TRANSMITTER

Operating Frequency: 418 MHz  
Addresses: 16,777,216 unique addresses  
Membrane Keypad: 8 keys

### RECEIVER

4 SPDT relay outputs

- Momentary (active while key pressed)
- Latched (alternates active with each key press)
- Pulsed (duration programmable from 1 ms to 10 seconds)

2 RS232 serial ports

- Each port has 2 transmitter keys associated with it
- Each port is user-programmable for Baud Rate, Data Bits, Stop Bits and Parity
- Each associated key is user-programmable with up to a 50 character data string, which is sent when the key is pressed

### EXTERNAL COMPUTER INTERFACE

Proprietary PC-based programming software is provided  
Proprietary programming cable is provided

Specifications subject to change.



The Windows-based Graphical User Interface is incredibly easy to use.

